

Approx. finished size: 2T - 3T and [4T - 5T]

## Wild Animal Hooded Robes

Shown in the Mosaic Blooms collection by Winthur Sempliner for Connecting Threads  $^{\! \otimes \! }$ 

## Alligator Fabrics



8369 Petals Lime

2-1/4 yds [2-1/2 yds]

2

3949 Soid Sprout

2-1/4 yds [2-1/2 yds]



6699 Faux Burlap

Lime

I yd

#### Additional Supplies Needed:

I I" square fusible fleece
I 3" square fusible web
Stuffing for eyeballs
Scrap of solid white fabric approx. I 3" square
Scrap of solid black fabric approx. 5" square
Tracing paper to copy pattern (optional)

### Fox Fabrics



8376 Diamonds and Dots Sky

2-1/4 yds [2-1/2 yds]



3947 Solid

Sky

2-1/4 yds [2-1/2 yds]



6702 Faux Burlap Periwinkle

I yd both sizes

Note: Larger size is shown in brackets when it differs.

Pattern is 24 pages long; please print the desired pages. Pages 2-8 Alligator Head and Robe instructions. Pages 9-15 Fox Robe Head and Robe instructions Pages 16-24 Pattern pieces for both robes.



Approx. finished size: 2T - 3T and [4T - 5T]

# Alligator Hooded Robe

Shown in the Mosaic Blooms collection by Winthur Sempliner for Connecting Threads®

## **Fabrics**



8369 Petals Lime

2-1/4 yds [2-1/2 yds]

2

3949 Soid Sprout

2-1/4 yds [2-1/2 yds]



6699 Faux Burlap Lime

I yd

Note: larger size is shown in brackets when it differs.

### Additional Supplies Needed:

II" square fusible fleece

13" square fusible web

Stuffing for eyeballs

Scrap of solid white fabric approx. 13" square

Scrap of solid black fabric approx. 5" square Tracing paper to copy pattern (optional)

# Alligator Hooded Robe

## Pattern Basics

We encourage breaking the rules, but here are a few things you might want to keep in mind:

- Please read through all the instructions carefully before beginning a project. Every effort has been made to ensure the accuracy of this pattern.
- All instructions use a 1/2" seam allowance unless otherwise stated.
- Back stitch at the start and end of each line of stitching.
- Need help with any of the techniques used?
   Check out our free tutorials and videos at www.connectingthreads.com/tutorials/quilting\_tutorials.html

### Common Quilting Acronyms:

 $FQ = fat quarter (18" \times 22")$ 

WOFQ = width of fat quarter

WOF = width of fabric

LOF = length of fabric

WS = wrong side of fabric

RS = right side of fabric

RST = right sides together

WST = wrong sides together

HST = half square triangle

QST = quarter square triangle



Approx. finished size: 2T - 3T and (4T - 5T)



A - Front cut one pair

B - Back cut one

C - Sleeves cut one pair

D - Hood cut one pair

Head - cut one pair

Eyelids - cut one pair

[2-1/2 yds]

**H** - Front lining cut one pair

I - Back lining cut one

K - Hood lining cut one pair

L - Sleeve lining cut one pair

2-1/4 yds [2-1/2 yds]

E - Cuff cut 2 pairs

 ${f F}$  - Belt cut two 32"  $\times$  8"

 $\boldsymbol{G}$  - Belt loops cut two 4"  $\times$  3"

I yd

#### Additional cutting instructions:

Scrap of solid white fabric approx. 13" square:

Eye - cut one pair

Teeth - cut two 2-1/2" x 13" strips

Scrap of solid black fabric approx. 5" square:

Pupils - cut one pair

Nostrils - cut one pair

For the larger size 4T - 5T, add 4" to the bottom of front A, back B, lining front H and lining back J.

Note: Larger size is shown in brackets when it differs


## Cutting Suggestions

Fabrics 1, 2, and 3 are folded in half lengthwise with WS together and selvages aligned.

For the larger size 4T - 5T, add 4" to the bottom of front A, back B, lining front H and lining back J.

Yardage below is diagrammed on 40" width selvage to selvage. FQs are diagrammed on 20" width.

Maps for assembling paper templates - Trace or copy each pattern page 3 times. Construct each template by matching the color, symbols and center/grain lines.





## Make the Alligator Head:


I. Trace a pair of alligator pupils and nostrils onto the paper side of fusible web. Roughly cut out and following the manufacturer's instructions, iron the fusible web to the WS of the fabric. Cut exactly on the line. Position each pupil on the RS in the center of each eye. Iron in place and stitch around edge using either zigzag, blanket, satin, or straight stitch.









2. Lay each eye and eyelid RST matching the straight edge and stitch. Press the seam open.



3. Fold I/4" to the WS. Using a strong thread, run a basting stitch around the edge, just like a Yo-Yo. Gather the eyeball in and stuff. Tie off your thread. Repeat on other eye. Set aside.




- 4. Following the manufacturer's instructions, iron the fusible fleece to the WS of one head piece.
- 5. Position the nostrils on the RS of the other head piece and iron in place. Stitch around appliqué.




- 6. Iron a  $2-1/2" \times 13"$  strip of fusible web to the WS of the teeth fabric. Cut strip and fuse to the WS of remaining teeth fabric strip.
- 7. Use the teeth pattern and cut out teeth.




8. Starting 1/2" from the edge, pin the teeth to the RS of one of the head pieces. You may need to snip into the teeth seam allowance to enable the teeth to lay flat. Then sandwich the other head RST. Stitch around the edge leaving a 3" opening in the back of the head.



9. Cut the seam allowance back to 1/8" where stitched and turn RS out. Press the seam allowance in on the open edge and top stitch the opening closed 1/8" from the edge. Continue top stitching all the way around the head. Press.




10. Position the eyeballs and hand stitch in place. Set aside.




#### Make the Hooded Robe:


11. Lay **A** and **B** RST matching the shoulder seam. Stitch and press seam open. Sew the other **A** to **B**. Repeat with **H**s and **J** to make the lining of the robe.




12. Sew a basting stitch over each sleeve **C**, from front notch to double notch. Repeat with each **L**.



13. Pin the sleeve **C** in place RST matching the center notch with the shoulder seam **A/B**. Ease the sleeve in, using the basting thread, to fit the armhole. Stitch. Press to sleeve. Repeat with **L**s and **H/J**.



14. Pin the side seam and sleeve closed, matching the underarm seam. Stitch. Repeat with lining.




15. Make the cuff. Match tvhe short edges of **E** and stitch RST. Press the seam open. Repeat with remaining **E**s.


16. Slip one **E** inside another **E** RST. Match seam, and stitch around long edge. Turn the cuff RS out and press.




17. Slide the cuff over the end of the sleeve matching the seam. Baste the edges together.




- 18. Make the belt. Join the two **F**s RST end-to-end to make one long strip. Press the seam open.
- 19. Fold and press the belt in half WST to make a strip  $9-1/2" \times 62"$ . Open and fold the raw edges to the center. Press.




20. Fold and press 1/2" to the WS at each end of the belt. Fold the belt in half, matching the folded edges and stitch 1/8" from the edge all the way around the belt.




- 21. Make the belt loops **G**. Fold and press in the same way as above. Each belt loop should measure 3/4" x 3". Stitch 1/8" from the edge all the way around the belt. Set aside.
- 22. Make the hood. Lay the two **D**s RST and stitch across the straight edge at the top and the curved edge at the back. Press seams open.




straight line. Stitch. Repeat Steps 22 and 23 with Ks to make the hood lining.




24. Stitch the hood into the robe at the neckline RST. Clip into the seam allowance to help the seam lay flat. Press 28. Carefully turn the robe RS out. Press the seam allowance seam away from hood. Repeat with lining.




25. Lay the robe and the lining RST. Pin all the way around the hood and down each side of the front. Pin across the hem line leaving a 10" opening in the back hem. Starting at the back, stitch the robe to the lining, leaving a 10" opening in the back hem.




26. Turn the robe RS out and push the sleeve linings into place making sure the sleeves are not twisted. Fold 5/8" seam allowance of the lining between the robe and the lining. Fold the seam allowance from the cuff and the outside sleeve, inside with the lining seam allowance. Pin and stitch around the sleeve 1/8" from the folded edge through all layers.



23. Fold the hood so that the hole at the top becomes one 27. Reach inside the opening at the bottom of the robe and pinch together the hood and neckline seam allowance for the outside and the lining. Match the shoulder seams and stitch the back neckline seam allowances together, attaching the lining and the outside only through the seam allowance.



into the opening at the back. Press the edge and top stitch 1/4" from the edge all the way around.




29. Feel to match the side seam allowance. Pin the belt loops in place 5" below the underarm and stitch on the RS of the hooded robe through all layers.



30. Position and pin the head on the RS of hood with the nose extending I" past the front edge of the hood. Carefully stitch through all layers on top of 1/8" top stitching around edge of head.







Approx. finished size: 2T - 3T and [4T - 5T]

## Fox Hooded Robe

Shown in the Mosaic Blooms collection by Winthur Sempliner for Connecting Threads®

## **Fabrics**



8376 Diamonds and Dots Sky

2-1/4 yds [2-1/2 yds]

2

3947 Solid Sky

2 2-1/4 yds [2-1/2 yds]

3

6702 Faux Burlap Periwinkle

I yd both sizes

### Note: larger size is shown in brackets when it differs.

Additional Supplies Needed:

II" square fusible fleece

10" square fusible web

Black embroidery floss

Scrap of solid white fabric approx. 5" square

Scrap of solid black fabric approx. 5" square

Tracing paper to copy pattern (optional)

## Fox Hooded Robe

## Pattern Basics

We encourage breaking the rules, but here are a few things you might want to keep in mind:

- Please read through all the instructions carefully before beginning a project. Every effort has been made to ensure the accuracy of this pattern.
- All instructions use a 1/2" seam allowance unless otherwise stated.
- Back stitch at the start and end of each line of stitching.
- Need help with any of the techniques used? Check out our free tutorials and videos at www.connectingthreads.com/tutorials/quilting\_tutorials.html

### Common Quilting Acronyms:

 $FQ = \text{fat quarter } (18" \times 22")$ WOFQ = width of fat quarter RST = right sides together WOF = width of fabric WST = wrong sides together

LOF = length of fabric

WS = wrong side of fabric

RS = right side of fabric

HST = half square triangle

QST = quarter square triangle



Approx. finished size: 2T - 3T and (4T - 5T)

**A -** Front cut one pair

**B** - Back cut one

C - Sleeves cut one pair

D - Hood cut one pair

**Head** - cut one pair 2-1/4 yds

Ears - cut two pair

[2-1/2 yds]

**H** - Front lining cut one pair

J - Back lining cut one

**K** - Hood lining cut one pair

2-1/4 yds L - Sleeve lining cut one pair [2-1/2 yds]

**E** - Cuff cut two pair

F - Belt cut two 32" × 8"

G - Belt loops cut two 4" × 3"

I yd

Inner Ears - cut one pair Eyelids - cut one pair

Additional cutting instructions:

Scrap of solid white fabric approx. 5" square:

Eye - cut one pair

Sparkle - cut one pair

Scrap of solid black fabric approx. 5" square:

Nose - cut one

Pupil - cut one pair

For the larger size 4T - 5T, add 4" to the bottom of front A, back B, lining front H and lining back J.

Note: larger size is shown in brackets when it differs.

# Cutting Suggestions


Fabrics 1, 2, and 3 are folded in half lengthwise with WS together and selvages aligned.

For the larger size 4T - 5T, add 4" to the bottom of the front A and the back B, the lining front H and lining back J.

(K)(D) Fold () Pold B SELVAGES Head FOLD (A)(H)Ears (C) 2 Pupils (E) Inner Ears Nose G SELVAGES **○**○Eyes Sparkles 5 See Step I for cutting Fox Inner Ear and Fox Eye Lid;

Yardage below is diagrammed on 40" width selvage to selvage. FQs are diagrammed on 20" width.

Maps for assembling paper templates -Trace or copy each pattern page 3 times. Construct each template by matching the color, symbols and center/grain lines.



they are cut on single layer

(not folded) fabric.


Eyelids

SELVAGES




#### Make the Fox Head:


I. Prepare the appliqué pieces on page 7 by tracing them onto the paper side of the fusible web. Roughly cut out. Iron onto the WS of the fabrics. Cut out pieces exactly on the line.







2. To create the face, fuse the Step I appliqué pieces on the RS of one of the Head pieces. Stitch around each of the appliqué pieces.



- 3. Iron the fusible fleece to the WS of the other head piece.
- 4. Iron the fusible fleece to the WS of one pair of ears. Iron the appliqué Inner Ear to the RS of each of these.




5. Lay the other pair of ears RST to the appliquéd pair. Stitch around the two long sides. Cut the seam allowance back to 1/8" and turn RS out. Press









6. Stitch just inside the appliqué, through both layers of the



7. Fold each ear in half, appliquéd side in, and stitch a small dart in each ear and press to one side.




8. Lay the fox head RST and stitch around the edges as shown. Trim the seam allowance back to 1/8". Turn RS out and press. Fold and press the seam allowance into the opening in the head.



9. Tuck the ears into each corner of the head. Top stitch 1/8" from the edge all around the head, closing the opening and catching the ears in place.




10. Mark in whiskers and embroider.




#### Make the Hooded Robe:


11. Lay **A** and **B** RST matching the shoulder seam. Stitch and press seam open. Sew the other **A** to **B**. Repeat with **H**s and **J** to make the lining of the robe.




12. Sew a basting stitch over the curve in each **C** sleeve from front notch to double notch. Repeat with each **L**.



13. Pin the sleeve **C** in place RST matching the center notch with the shoulder seam **A/B**. Ease the sleeve in, using the basting thread, to fit the armhole. Stitch. Press to sleeve. Repeat with **L**s and **H/J**.



14. Pin the side seam and sleeve closed, matching the underarm seam. Stitch. Repeat with lining.




15. Make the cuff. Match the short edges of **E** and stitch RST. Press seam open. Repeat with the remaining **E**s.


16. Slip one **E** inside another **E** RST. Match seam, and stitch around long edge. Turn the cuff RS out and press.




17. Slide the cuff over the end of the sleeve matching the seam. Baste the edges together.




- 18. Make the belt. Join the two **F**s RST end-to-end to make one long strip. Press the seam open.
- 19. Fold and press the belt in half WST to make a strip  $9-1/2" \times 62"$ . Open and fold the raw edges to the center. Press.




20. Fold and press 1/2" to the WS at each end of the belt. Fold the belt in half, matching the folded edges and stitch 1/8" from the edge all the way around the belt.



- 21. Make the belt loops **G**. Fold and press in the same way as above. Each belt loop should measure 3/4" × 3". Stitch 1/8" from the edge all the way around the belt. Set aside.
- 22. Make the hood. Lay the two **D**s RST and stitch across the straight edge at the top and the curved edge at the back. Press seams open.




23. Fold the hood so that the hole at the top becomes one 27. Reach inside the opening at the bottom of the robe and straight line. Stitch. Repeat Steps 22 and 23 with Ks to make the hood lining.




24. Stitch the hood into the robe at the neckline RST. Clip seam away from hood. Repeat with lining.




25. Lay the robe and the lining RST. Pin all the way around the hood and down each side of the front. Pin across the hem line leaving a 10" opening in the back hem. Starting at the back, stitch the robe to the lining, leaving a 10" opening in the back hem.




26. Turn the robe RS out and push the sleeve linings into place making sure the sleeves are not twisted. Fold 5/8" seam allowance of the lining between the robe and the lining. Fold the seam allowance from the cuff and the outside sleeve, inside with the lining seam allowance. Pin and stitch around the sleeve 1/8" from the folded edge through all layers.



pinch together the hood / neckline seam allowance for the outside and the lining. Match the shoulder seams and stitch the back neckline seam allowances together, attaching the lining and the outside only through the seam allowance.



into the seam allowance to help the seam lay flat. Press 28. Carefully turn the robe RS out. Press the seam allowance into the opening at the back. Press the edge and top stitch 1/4" from the edge all the way around.



29. Feel to match the side seam allowance. Pin the belt loops in place 5" below the underarm and stitch on the RS of the hooded robe through all layers.



30. Position and pin the head on the RS of hood with the nose extending I" past the front edge of the hood. Carefully stitch through all layers on top of 1/8" top stitching around edge of head.



